

ST-HB42A1X



Brightness	500 cd/m
Contrast Ratio	1200:1
Viewing Angle	H:176 / V:176
Response Time	6.5ms (GTG)
Supported colors	16.7M
Resolution	1920 x 1080
Horizontal Frequency	30K ~ 65KHz
Vertical Frequency	56 ~ 75Hz
Input Resolution	1920 x 1080@60Hz (Analog) 1920 x 1080@60Hz (Digital)
DDC	DDC 2B
OSD Control	RS232C, Push button
OSD Language	English
Video Signal Type	RGB Analog / Digital
Connector	15 pin D-Sub / DVI / Component / S-video / AV / HD-SDI BNC x 3
Dimension W/O Stand	1026.0 x 619.0 x 121.6 mm (WxHxD) Diagonal 42.02"
Weight	Net: 29kg, Gross: 35kg
Wall / Arm Mount Type	200mm x 200mm / 200mm x 600mm VESA
Multimedia	PIP, PAP, Zoom
AV / TV	W/O TV Tuner
Fanless Design	Yes
Power Supply	AC 110V ~ 220V
Normal Operation	<250W
Suspend / Standby	<20W
Power Off Mode	<20W P
Communication Port	RS232C In / RJ 45 Out
Compliance	CE, FCC, VCCI, BSMI, CCC, CB, UL/CUL, TUV/ PS, ROHS/ WEEE

Digital Signage Display Application

